



US006254574B1

(12) **United States Patent**  
**Burzynski et al.**

(10) **Patent No.:** **US 6,254,574 B1**  
(45) **Date of Patent:** **Jul. 3, 2001**

(54) **SELF-BLUNTING NEEDLE MEDICAL DEVICES AND METHODS OF MANUFACTURE THEREOF**

(75) **Inventors:** **Mark J. Burzynski**, Southbury; **Alexander K. Jones**, Orange, both of CT (US); **Richard S. Kearns**, Seattle, WA (US); **John M. Polidoro**; **Carl R. Sahi**, both of Coventry, CT (US); **Chad C. Smutney**, Stafford Springs, CT (US)

(73) **Assignee:** **Bio-Plexus, Inc.**, Vernon, CT (US)

(\*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** **09/360,877**

(22) **Filed:** **Jul. 23, 1999**

**Related U.S. Application Data**

(63) Continuation-in-part of application No. 08/772,002, filed on Dec. 19, 1996, now Pat. No. 5,951,520.

(51) **Int. Cl.<sup>7</sup>** ..... **A61M 5/178**

(52) **U.S. Cl.** ..... **604/170.01; 604/506**

(58) **Field of Search** ..... **604/158, 110, 604/159, 161, 162, 164.01, 164.07, 164.08, 164.09, 170.01**

(56) **References Cited**

**U.S. PATENT DOCUMENTS**

1,527,291	2/1925	Zorraquin .	
3,491,756	1/1970	Bentov .	
3,536,073	10/1970	Farb .	
3,585,996 *	6/1971	Reynolds	604/158
3,809,081	5/1974	Loveless .	
4,068,659 *	1/1978	Moorehead	604/159
4,121,588	10/1978	Geiger .	
4,233,975	11/1980	Yerman .	
4,274,408	6/1981	Nimrod .	
4,525,157	6/1985	Vaillancourt	604/510

4,529,399	7/1985	Groshong et al.	604/510
4,613,329	9/1986	Bodicky	604/158
4,627,841	12/1986	Dorr	604/158
4,675,005	6/1987	DeLuccia	604/110
4,721,506	1/1988	Teves	604/506
4,801,295	1/1989	Spencer	604/198
4,808,169	2/1989	Haber et al.	604/195
4,810,248	3/1989	Masters et al.	604/192
4,828,547 *	5/1989	Sahi et al.	604/164.06

(List continued on next page.)

**Primary Examiner**—Anhtuan T. Nguyen

(74) **Attorney, Agent, or Firm**—Libert & Associates; Frederick A. Spaeth

(57) **ABSTRACT**

A self-blunting needle medical device comprises a needle cannula (18) fixed to a hub (20) having a receiving structure therein such as ferrule (22) and a movable blunting member (14) movably received within the cannula (18). Ferrule (22) defines a passage (38) extending therethrough, within which both the cannula (18) and the movable member (14) can be received and which establishes a coaxial relationship between them. The ferrule (22) defines a first guide surface (40) for directing the blunting end (14a) of the movable member (14) into the central bore of the cannula (18) during assembly. A second guide surface (42) performs the function of guiding the mounting end (18b) of the cannula (18) into ferrule (22) for mounting therein. Typically, the cannula (18) has a tissue puncture tip (18a). When the movable member (14) is retracted into the cannula (18), the puncture tip (18a) is exposed for use, e.g., injection into tissue. The movable member (14) is then moved to an extended position in which blunting end (14a) projects beyond the puncture tip (18a), to render the device safe with regard to subsequent accidental needle sticks. Methods of assembling the self-blunting needle are also presented. In various embodiments, the guide member may be integral with the assembled device or may be defined by a guide member that is used only in the assembly process and from which the assembled device may be removed.

**28 Claims, 9 Drawing Sheets**

